


REFRIGERATED UNITS

TRANSPORT



*You make the ice.
We'll help you sell it.*

Refrigerated Transport Unit			Exterior Dimensions			Interior Dimensions			Door Opening	Weight		CFC-Free Refrigeration <small>(see "options" for special refrigeration)</small>		Truck Size Required <small>(verify truck weight capacity and box dimensions before ordering)</small>		
Models	Capacity		Width	Length	Height	Width	Length	Height	Width x Height	Crated	Uncrated	Size	Amps	Pick-Up	Trailer	
	Cu. Ft. <small>(approx)</small>	Bags* <small>(7 lb.)</small>													Pallet Size	Quantity
4 x 8 CP	140	570	48"	96"	71"	42"	90"	65"	25" x 57"	1175 lbs.	935 lbs.	3/4 hp	10.4	3/4 Ton	X	X
4 x 8 AD	140	550	48"	96"	71"	42"	90"	65"	25" x 57"	1085 lbs.	845 lbs.	1/2 hp	9.6	3/4 Ton	X	X
5 x 9 CP	220	740	56"	108"	83"	50"	102"	76"	45" x 74"	1795 lbs.	1415 lbs.	3/4 hp	10.4	X	42" x 48"	2
5 x 9 AD	220	720	56"	108"	83"	50"	102"	76"	45" x 74"	1640 lbs.	1260 lbs.	3/4 hp	11.6	X	42" x 48"	2

MODEL IDENTIFICATION

Model Letter Suffix: "CP" = Coil Plate
"AD" = Automatic Defrost

STANDARD FEATURES—ALL MODELS

- ▶ Steel cabinet construction
- ▶ High gloss polyester FDA Tonka White finish exterior
- ▶ Stucco galvanized finish interior
- ▶ 3" thick, CFC-free, foamed in place polyurethane insulation in all walls, top and bottom
- ▶ Heavy-duty powder-coated hinges and lockable latch
- ▶ Interior safety release handle
- ▶ R404A-115/1/60 semi hermetic refrigeration
- ▶ Interior lighted switch and vapor-proof light fixtures
- ▶ Thermostat control
- ▶ Dial thermometer
- ▶ 20' power cord with electric control box
- ▶ Magnetic door gaskets
- ▶ Door rain shield
- ▶ Automatic defrost or coil plate refrigeration system
- ▶ One year compressor and parts warranty
- ▶ Wood duckboard floor overlay on 4 x 8 *(see photo)*



Coil Plate Interior
(4 x 8 Shown)



* Merchandiser storage capacity may vary due to type of ice, ice bag size differences and methods of loading.

ⓘ 20 amp circuit recommended

STANDARD FEATURES 5 X 9 MODELS

- ▶ 4" thick polyurethane insulated floor
- ▶ 14 gauge galvanized floor surface
- ▶ Stainless steel locking door hardware
- ▶ Balloon door gaskets
- ▶ Interior door kick treadplates, pallet skid rails and pallet stop *(see photo)*



Auto Defrost Interior
(5 x 9 Shown)

OPTIONS

- ▶ Strip curtain (recommended for -10°F)
- ▶ -10°F freezer or 35°F cooler (R134a)
- ▶ Heavy-duty refrigeration (automatic defrost models only)
230/1/60 required for 5 x 9

NOTE:

These large-capacity, heavy-duty refrigerated transport units permit easy loading, easy access and controlled-temperature delivery for a variety of frozen or refrigerated products.

Material and product improvement is a constant commitment at Leer, Inc. These specifications are subject to change without notice and without incurring responsibility for previously sold merchandisers and components.



We convert cold to sold.™

Leer, Inc. • 206 Leer Street, New Lisbon, WI 53950 • 800.766.5337 • leerinc.com

